

THOMSON
DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

[Log Out](#) | [My Account](#) | [Products](#)
[Search: Quick/Number Boolean Advanced](#)

The Delphion Integrated View

 Get Now: ☒ PDF | [More choices...](#)

 Tools: Add to Work File: [Create new Wor...](#)

 View: [INPADOC](#) | Jump to: [Top](#)

 Go to: [Derwent...](#)
[Email](#)

Title: JP3222257A2: MANUFACTURE OF LITHIUM ELECTRODE FOR LITHIUM BATTERY

Country: JP Japan

Kind: A

Inventor: NAGaura TORU;
YOKOGAWA MASAaki;
NAKAO TOSHIHIKO;
SATO KATSUZO;

Assignee: SONY CORP.
[News, Profiles, Stocks and More about this company.](#)

Published / Filed: 1991-10-01 / 1990-01-25

Application Number: JP1990000015768

IPC Code: [H01M 4/04](#); [H01M 4/64](#);

Priority Number: 1990-01-25 JP1990000015768

Abstract:

PURPOSE: To prevent the adhesion of lithium in a rolled state and the breakage of a lithium foil during operation up to battery assembly for efficient operation by press-attaching the lithium foil formed by extrusion directly to a metal collector foil before winding in a rolled state.

CONSTITUTION: A copper foil rolled substance 22 that a copper foil 21 is wound in a rolled state and an extruder 24 for a lithium foil 23 are prepared to have the one face of the copper foil 21, supplied from the copper foil rolled substance 22, and the desired-thickness lithium foil 23, extruded and molded from the extruder 24, faced in opposition, passed through a pair of pressure rollers 25, press-attached to each other and then wound in a rolled state. In this case, for making the lithium foil 23 thin up to a desired thickness, the lithium foil 23 from the extruder 24 is given cold rolling via 4-step rolls 26-29 and cold rolling mechanism 30. It is thus possible to prevent the adhesion of lithium in a rolled state and the breakage of the lithium during operation up to battery assembly for efficient operation.


COPYRIGHT: (C)1991,JPO&Japio.

INPADOC Legal Status: None [Get Now: Family Legal Status Report](#)

Family: [Show 2 known family members](#)

Other Abstract Info: DERABS C91-330151 DERC91-330151.






[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)

THOMSON  DELPHION		RESEARCH	PRODUCTS	INSIDE DELPHION
Home	About Delphion	My Account	Products	Search: Quick/Number Boolean Advanced

The Delphion Integrated View

Get Now: <input checked="" type="checkbox"/> PDF More choices...	Tools: Add to Work File: Create new Wor
View: INPADOC Jump to: Top	Go to: Derwent...

Title: **JP3222257A2: MANUFACTURE OF LITHIUM ELECTRODE FOR LITHIUM BATTERY**

Country: **JP Japan**
 Kind: **A**

Inventor: **NAGAURA TORU;
YOKOGAWA MASAOKI;
NAKAO TOSHIHIKO;
SATO KATSUZO;**

Assignee: **SONY CORP**
[News, Profiles, Stocks and More about this company](#)

Published / Filed: **1991-10-01 / 1990-01-25**

Application Number: **JP1990000015768**

IPC Code: **H01M 4/04; H01M 4/64;**

Priority Number: **1990-01-25 JP1990000015768**

Abstract:

PURPOSE: To prevent the adhesion of lithium in a rolled state and the breakage of a lithium foil during operation up to battery assembly for efficient operation by press-attaching the lithium foil formed by extrusion directly to a metal collector foil before winding in a rolled state.

CONSTITUTION: A copper foil rolled substance 22 that a copper foil 21 is wound in a rolled state and an extruder 24 for a lithium foil 23 are prepared to have the one face of the copper foil 21, supplied from the copper foil rolled substance 22, and the desired-thickness lithium foil 23, extruded and molded from the extruder 24, faced in opposition, passed through a pair of pressure rollers 25, press-attached to each other and then wound in a rolled state. In this case, for making the lithium foil 23 thin up to a desired thickness, the lithium foil 23 from the extruder 24 is given cold rolling via 4-step rolls 26-29 and cold rolling mechanism 30. It is thus possible to prevent the adhesion of lithium in a rolled state and the breakage of the lithium during operation up to battery assembly for efficient operation.

COPYRIGHT: (C)1991,JPO&Japio

INPADOC: **None** Get Now: [Family Legal Status Report](#)

Legal Status:

Family: [Show 2 known family members](#)

Other Abstract Info: **DERABS C91-330151 DERC91-330151**






[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion . . . [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)



(19)

(11) Publication number:

03

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **02015768**(51) Intl. Cl.: **H01M 4/04 H01M 4/64**(22) Application date: **25.01.90**

(30) Priority:	(71) Applicant: SONY CORP
(43) Date of application publication: 01.10.91	(72) Inventor: NAGAURA TORU YOKOGAWA MASAOKI NAKAO TOSHIHIKO SATO KATSUZO
(84) Designated contracting states:	(74) Representative:

**(54) MANUFACTURE OF
LITHIUM ELECTRODE FOR
LITHIUM BATTERY**


(57) Abstract:

PURPOSE: To prevent the adhesion of lithium in a rolled state and the breakage of a lithium foil during operation up to battery assembly for efficient operation by press-attaching the lithium foil formed by extrusion directly to a metal collector foil before winding in a rolled state.

CONSTITUTION: A copper foil rolled substance 22 that a copper foil 21 is wound in a rolled state and an extruder 24 for a lithium foil 23 are prepared to have the one face of the copper foil 21, supplied from the copper foil rolled substance 22, and the desired-thickness lithium foil 23, extruded and molded from the extruder 24, faced in opposition, passed through a pair of pressure rollers 25, press-attached to each other and then wound in a rolled

state. In this case, for making the lithium foil 23 thin up to a desired thickness, the lithium foil 23 from the extruder 24 is given cold rolling via 4-step rolls 26-29 and cold rolling mechanism 30. It is thus possible to prevent the adhesion of lithium in a rolled state and the breakage of the lithium during operation up to battery assembly for efficient operation.

COPYRIGHT: (C)1991,JPO&Japio





(19)

(11) Publication number:

03

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **02015768**(51) Intl. Cl.: **H01M 4/04 H01M 4/64**(22) Application date: **25.01.90**

(30) Priority:	(71) Applicant: SONY CORP
(43) Date of application publication: 01.10.91	(72) Inventor: NAGaura TORU YOKOGAWA MASAaki NAKAO TOSHIIKO SATO KATSUZO
(84) Designated contracting states:	(74) Representative:

**(54) MANUFACTURE OF
LITHIUM ELECTRODE FOR
LITHIUM BATTERY****(57) Abstract:**

PURPOSE: To prevent the adhesion of lithium in a rolled state and the breakage of a lithium foil during operation up to battery assembly for efficient operation by press-attaching the lithium foil formed by extrusion directly to a metal collector foil before winding in a rolled state.

CONSTITUTION: A copper foil rolled substance 22 that a copper foil 21 is wound in a rolled state and an extruder 24 for a lithium foil 23 are prepared to have the one face of the copper foil 21, supplied from the copper foil rolled substance 22, and the desired-thickness lithium foil 23, extruded and molded from the extruder 24, faced in opposition, passed through a pair of pressure rollers 25, press-attached to each other and then wound in a rolled

state. In this case, for making the lithium foil 23 thin up to a desired thickness, the lithium foil 23 from the extruder 24 is given cold rolling via 4-step rolls 26-29 and cold rolling mechanism 30. It is thus possible to prevent the adhesion of lithium in a rolled state and the breakage of the lithium during operation up to battery assembly for efficient operation.

COPYRIGHT: (C)1991,JPO&Japio

